



Sumoto		C.S.C.R. Type												
IP 44	KW	0,37	0,55	0,75	1,1	1,5	2,2	3,7	Hz 50/60					
⚡	Power voltage	V 110			V 220		V 230							
	Capacitor run	16	20	25	30	35	40	60	80	100				
⚡	Capacitor start													
	Thermal protection	25	30	35	40	75	90	140	200	300				
CE	Amp.	4	5	6	7	8	9	10	12	14	15	16	20	25

Attenzione!
Prima di rimuovere il coperchio togliere la tensione di rete

Warning!
Before remove the cover take off the electric power

Series CONTROL BOX

FOR SINGLE PHASE SUBMERSIBLE ELECTRIC MOTOR

CONTROL BOX

for single phase submersible electric motor

PSC Series

Technical features

- Enclosure made out of ABS.
- Switch on-off.
- Thermal protection with manual reset.
- Running capacitor.
- Cable glands.
- Range: from 0.37kW to 2.2kW.

PSC A Series Dimensions: 180 x 150 x 70 mm.

PSC B Series Dimensions: 195 x 150 x 80 mm.



CSCR Series

Technical features

- Enclosure made out of ABS.
- Switch on-off.
- Thermal protection with manual reset.
- Starting capacitor and running capacitor.
- Potential starting relay.
- Cable glands.
- Lightning arrestor.
- Range: from 0.37kW to 2.2kW.

CSCR A Series Dimensions: 195 x 150 x 80 mm.

CSCR B Series Dimensions: 240 x 190 x 90 mm.

CSCR 3.7Kw Series:

- Double starting capacitor and double running capacitor
- Range: 3.7kW
- Dimensions: 310 x 230 x 150 mm.



CONTROL BOX

for single phase submersible electric motor

METAL CONTROL BOX

Technical features

- Enclosure made in painted steel.
- Available in:
 - PSC running capacitor
 - CSCR starting capacitor and running capacitor
 - CSIR starting capacitor/induction run.
- Voltmetric relay.
- Suitable for indoor and outdoor installation.
- External access to thermal protection.
- Range:
 - PSC: from 0,37kW to 2,2kW
 - CSIR: from 0,37kW to 3,7kW
 - CSCR: from 0,37kW to 0,75kW.

